



JOB/P.O. \_\_\_\_\_ Date \_\_\_\_\_ Sales Person \_\_\_\_\_ Page \_\_\_\_\_  
 Company \_\_\_\_\_ Street \_\_\_\_\_  
 Cont. Person \_\_\_\_\_ City/State \_\_\_\_\_  
 Phone \_\_\_\_\_ Zip Code \_\_\_\_\_  
 Fax \_\_\_\_\_ Email \_\_\_\_\_


Shutter # \_\_\_\_\_ Product: \_\_\_\_\_  No Light Slits  E.R. System  
 Box Color: \_\_\_\_\_ Slat Color: \_\_\_\_\_ Base Slat Color: \_\_\_\_\_ Rail Color: \_\_\_\_\_  
 Box Shape  45°  90°  
 Width: \_\_\_\_\_  FM  Opening  
 Height: \_\_\_\_\_  FM  Rail Height

Rail Size	<input type="checkbox"/> 2.125"	<input type="checkbox"/> 2.5"	<input type="checkbox"/> 3"	<input type="checkbox"/> 3" HS	<input type="checkbox"/> 3" ER	<input type="checkbox"/> 3.5" ER	<input type="checkbox"/> 3.75" ER	Sills	<input type="checkbox"/> U Channel 
Rail Hole Size	<input type="checkbox"/> 1/2"	<input type="checkbox"/> 5/8"	<input type="checkbox"/> _____ inch	<input type="checkbox"/> no holes	<input type="checkbox"/> other	<input type="checkbox"/> 3cm cut		<input type="checkbox"/> L Angle 	
Rail Hole Distance	<input type="checkbox"/> Standard 12"	<input type="checkbox"/> _____ inch	<input type="checkbox"/> recessed						


Operator:	<input type="checkbox"/> REG	<input type="checkbox"/> RTS/HZ	<input type="checkbox"/> CMO/DMI	<input type="checkbox"/> RTSCMO	<input type="checkbox"/> ROLLAC
Motor:	<input type="checkbox"/> GEAR	<input type="checkbox"/> REC. BOX	<input type="checkbox"/> CRANK BOX	<input type="checkbox"/> PUSH/PULL	<input type="checkbox"/> SIMU
Others:					<input type="checkbox"/> SOMFY

Location: (side viewed from inside)  
 Left  Right  
 Axle:  
 Steel  Aluminum

Left Side



Right Side



Operator Position  
 A  D  G  
 B  E  
 C  F

Remote / Transmitter:	Switch Options:	White	Ivory	1 Pole	2 Pole
<input type="checkbox"/> Single Channel	<input type="checkbox"/> Maintained	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Multi Channel	<input type="checkbox"/> Momentary	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Wall Switch	<input type="checkbox"/> Key switch	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/> Other _____	<input type="checkbox"/> Key Pad	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/> Toggle				
	<input type="checkbox"/> Rocker				
	<input type="checkbox"/> Paddle				
	<input type="checkbox"/> Other _____				

Gear and Override Options

- Removable Crank - 46" with 2 hole universal
- Fixed Crank - 46" with 2 hole universal
- Special Crank for concealed operation - 53"

Base Slat Lock:  Slide  Cylinder  Commercial

Lock Position:  
 A (Back)  
 B (Coil Side)

Thumb Turn Position:  
 A (Back)  
 B (Coil Side)

